

FOR SMALL PROJECTS, STUCCO or RETAIL POINT-OF-SALE

- **HIGH PERFORMANCE CRACK CONTROL FIBERS**

NYCON CONTROL nylon fibers are ideal for improving any concrete or cement-based product. Adding CONTROL will significantly reduce plastic shrinkage cracking and provide a better concrete.

- **EASY PACK**

NYCON CONTROL fibers are proven to dramatically reduce cracking in any concrete and stucco projects. For a few dollars you or your customer can ensure projects will have less cracking, be more durable and last longer!

- **FOR POINT-OF SALE DISPLAY**

NYCON CONTROL fibers don't take up a lot of space, giving you a high space-to-profit ratio. With convenient tabletop and hanging display options, you can maximize exposure in your cement section or at check-out.

BAG DIMENSIONS - 6"W x 9"H x 1/2"D

BAG NET WEIGHT - 3oz

NYCON "PEG-BOARD" DISPLAY



NYCON "COUNTER-TOP" DISPLAY



800-456-9266

www.nycon.com

NYCON HANGING "CLIP-STRIP" DISPLAY



BENEFITS OF NYCON CONTROL

- Reduce Concrete Cracking
- High Resistance to Alkali and Corrosion
- Improve Impact Resistance
- Does not float to the surface of the concrete
- No "fuzzy" surface

Directions for Use

One 3-ounce (84 gr) bag of Nycon CONTROL Fibers to 300-350 pounds (136-159 kg) of mix, equivalent to one bag of CONTROL per bag of cement plus other ingredients.

Mixing Instructions

1. Mix dry ingredients with water according to mix requirements.
2. Add the proper dose of Nycon CONTROL Fibers.
3. Mix for approximately 4 minutes to allow mixing of fibers.

Packaging

Box - (150) 3oz bags

Point-of-Sale Box - (36) 3oz bags

Clip Strips - (36) 3 oz bags

***NYCON CONTROL** fibers comply ASTM C1116 Section 4.1.3 and meet requirements for plastic shrinkage in accordance with AC32 when used in proper dose.*



800-456-9266
www.nycon.com