

NYCON-P-TURF
 Polypropylene, Medium Denier, Fibrillated Fiber Tape



COST EFFECTIVE SOIL REINFORCEMENT
 NYCON-P-TURF, a cost-effective fiber, provides engineered root-zone and soil stabilization. NYCON-P-TURF offers a root interlocking reinforced turf matrix.



NYCON-P-TURF Physical Properties

Filament Diameter	0.03" (0.76 mm)
Fiber Length	0.75" (19 mm) to 2" (50 mm)
Specific Gravity	0.91
Tensile Strength	44 ksi (300 MPa)
Flexural Modulus	700 ksi (4.9 GPa)
Melting Point	320° F (160° C)
Color	White or Green
Water Absorption	Nil
Chemical Resistance	Excellent
Corrosion Resistance	High

Description

NYCON-P-TURF is incorporated into the soil profile at a depth of 4-6 inches where the fiber acts as a mass of indestructible roots. The turf roots intertwine and interlock with the fibers resulting in reinforced turf that is strong and resists divoting and rutting.

Applications

NYCON-P-TURF fibers help provide a consistent surface that can be worked and maintained with conventional equipment. They are designed specifically for easy spreading, mixing and grading. Fiber reinforcement can be used for complete field stabilization or in selected high-wear areas.

NYCON-P-TURF

Polypropylene, Medium Denier, Fibrillated Fiber Tape



Advantages/Benefits	<ul style="list-style-type: none">• Mechanical bond with the matrix• Reduces the formation of cracking• Provides multi-dimensional reinforcement• Enhances durability and toughness
Mixing	NYCON-P-TURF can be added and mixed into the soil in-situ after spreading the product over surface. NYCON-P-TURF has a normal recommended dosage rate of 6 lb/cy for 12 lb/cy of soil.
Packaging	(20) 30 lb boxes per pallet, 600 lbs per pallet Bulk supersacks
Storage and Shelf Life	NYCON-P-TURF should be stored in dry warehouse. Protect product from the rain.

KEEP CONTAINER TIGHTLY CLOSED - KEEP OUT OF REACH OF CHILDREN - NOT FOR INTERNAL CONSUMPTION - FOR INDUSTRIAL USE ONLY
All information provided by Nycon Corporation concerning Nycon products, including but not limited to, any recommendations and advice relating to the application and use of Nycon products, is given in good faith based on Nycon's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Nycon's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Nycon's control are such that Nycon assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Nycon product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s).

Nycon reserves the right to change the properties of its products without notice. All sales of Nycon product(s) are subject to its current terms and conditions of sale which are available at www.nycon.com or by calling 800-456-9266.

Prior to each use of any Nycon product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Material Safety Data Sheet which are available. Nothing contained in any Nycon materials relieves the user of the obligation to read and follow the warnings and instruction for each Nycon product as set forth in the current Product Data Sheet, product label and Material Safety Data Sheet prior to product use.

Nycon warrants this product for one year from date of shipment to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Nycon SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. Nycon SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

800-456-9266	www.nycon.com	sales@nycon.com
---------------------	---	---